



5.118 Inch | 130 Millimeter x 9.055 Inch | 230 Millimeter x 1.575 Inch | 40 Millimeter SKF NU 226 ECM/C3 Cylindrical Roller Bearings

Bearing No. NU 226 ECM/C3

NU 226 ECM/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	7.518
EAN	7316577054326
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	130MM Bore; Straight Bore Profile; 230MM Outside Diameter; 40MM Width;



NTN BEARING MANUFACTURING DE MEXICO,S...

	Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inte
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 226 ECM/C3
Weight / LBS	16.559
B	1.575 Inch 40 Millimeter
d	5.118 Inch 130 Millimeter
D	9.055 Inch 230 Millimeter
bore diameter:	130 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	230 mm
maximum rpm:	3400 RPM
overall width:	40 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	40 mm



NTN BEARING MANUFACTURING DE MEXICO,S...

operating temperature range:	Maximum of +300 ° F
fillet radius:	2.5 mm
dynamic load capacity:	415 kN
series:	NU2
static load capacity:	455 kN